

Material: **Ceramic** | Appearance: **Uniform** | Application: **Walls**

11

Colours

2

Finishes

4

Tile sizes

# Reta Matt

Reta offers a range of bevelled and flat wall tiles in two metro formats 100x300 and 75x150mm, available in a matt or gloss finish.




Shade variation: V1 - Uniform



### Bevelled

### Flat

|   | Sizes (mm) | >  <  | Finishes |
|---|------------|-------|----------|
| 1 | 100x300    | 7.5mm | Matt     |
| 2 | 75x150     | 5.8mm | Matt     |
| 3 | 75x150 BN1 | 5.8mm | Matt     |
| 4 | 75x150 BN2 | 5.8mm | Matt     |



LRV and PTV values can vary batch to batch, please contact for advice.  
Swatch colours may vary, samples should be requested.



Material: **Ceramic** | Appearance: **Uniform** | Application: **Walls**

11

Colours

1

Finish

1

Tile size

# Reta Gloss

Reta offers a range of bevelled and flat wall tiles in two metro formats 100x300 and 75x150mm, available in a matt or gloss finish.



Shade variation: V1 - Uniform



Bevelled

CICF53331BEV

CICF53332BEV

CICF53333BEV

CICF53334BEV

CICF53335BEV

CICF53336BEV

CICF53337BEV

CICF53338BEV

CICF53339BEV

CICF53340BEV

CICF53341BEV

Flat

CICF53331F

CICF53332F

CICF53333F

CICF53334F

CICF53335F

CICF53336F

CICF53337F


CICF53338F

CICF53339F

CICF53340F

CICF53341F

|   | Sizes (mm) | >  <  | Finishes |
|---|------------|-------|----------|
| 1 | 100x300    | 7.5mm | Matt     |
| 2 | 75x150     | 5.8mm | Matt     |
| 3 | 75x150 BN1 | 5.8mm | Matt     |
| 4 | 75x150 BN2 | 5.8mm | Matt     |



LRV and PTV values can vary batch to batch, please contact for advice.  
Swatch colours may vary, samples should be requested.



CICB49044BEV CICB49037BEV

Material: **Ceramic** | Appearance: **Uniform** | Application: **Walls**



# Reta



Above  
Wall: CICB49042 CICF53338BEV

Right  
Wall: CICB49044BEV CICF53340BEV



Above  
Wall: CICF53331BEV

LRV and PTV values can vary batch to batch, please contact for advice.  
Swatch colours may vary, samples should be requested.

[www.grestec.co.uk](http://www.grestec.co.uk) | T: 0345 130 2241 | E: [sales@grestec.co.uk](mailto:sales@grestec.co.uk)

Find us on:    

Material: **Ceramic** | Appearance: **Uniform** | Application: **Walls**



# Reta

## Technical data sheet - ISO 10545 average values

|    |                                                                                                                                                                     |                                                                                   |
|----|---------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|
| 3  | Water absorption                                                                                                                                                    | $18\% \leq E_b < 20\%$                                                            |
| 4  | Modulus of rupture                                                                                                                                                  | $\geq 13 \text{ N/mm}^2$                                                          |
| 4  | Breaking strength                                                                                                                                                   | $\geq 7,5 \text{ mm} \geq 660 \text{ N}$<br>$< 7,5 \text{ mm} \geq 220 \text{ N}$ |
| 8  | Linear thermal expansion coefficient                                                                                                                                | $6,0 - 8,0 \times 10^{-6} \text{ K}^{-1}$                                         |
| 9  | Thermal shock resistance                                                                                                                                            | <b>Conforms</b>                                                                   |
| 11 | Tensile strength                                                                                                                                                    | <b>Conforms</b>                                                                   |
| 12 | Frost resistance                                                                                                                                                    | <b>No</b>                                                                         |
| 13 | Chemical resistance<br>Low acid and base concentrations<br>Resistance to Acids and Alkalis of High Concentration<br>Household chemicals and swimming pool additives | <b>GLA</b><br><b>NPD</b><br><b>GA</b>                                             |
| 14 | Stain resistance                                                                                                                                                    | <b>Class 5</b>                                                                    |

## Sustainability information



## Cleaning and maintenance advice

### Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Cloth

### Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

Please see [www.filasolutions.com](http://www.filasolutions.com) for methods of use, dilution and coverage.

LRV and PTV values can vary batch to batch, please contact for advice.  
Swatch colours may vary, samples should be requested.

[www.grestec.co.uk](http://www.grestec.co.uk) | T: 0345 130 2241 | E: [sales@grestec.co.uk](mailto:sales@grestec.co.uk)

Find us on:    