

Material: **Ceramic** | Appearance: **Handcrafted** | Application: **Walls**

26

Colours

3

Finishes

2

Tile sizes

Thassos

Thassos presents a collection of ceramic wall tiles with a handcrafted style with slight undulation and a gloss, crackle or metallic finish.



Shade variation: V2 moderate



AWS9064 AWS38171 AWS38172 AWS38173 AWS38174 AWS38175 AWS9073



AWS9069 AWS38170 AWS38164 AWS9070 AWS9658 AWS9065 AWS9066




AWS9071 AWS9067 AWS9068

Crackle



AWS9060 AWS9061 AWS9062 AWS9063 AWS38191 AWS38104 AWS38192

Metallic



AWS45072 AWS45073



LRV and PTV values can vary batch to batch, please contact for advice.
Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:



Thassos



Formats

		AWS																									
		9064 38171 38172 38173 38174 38175 9073 9069 38170 38164 9070 9658 9065 9066 9071 9067 9068 x9060 9061 9062 9063 38191 38104 38192 45072 45073																									
Sizes (mm)	Thickness																										
1 75x150	9mm																										
2 130x130	9mm																										
3 75x130 moldura	9mm																										
4 50x130 moldura	9mm																										
5 50x150 moldura	9mm																										
6 20x150 torelo	9mm																										





Thassos

Technical data sheet - ISO 10545 average values

2	Sizes	Conforms
3	Water absorption	16-16%
4	Bending strength	Conforms
8	Thermal expansion coefficient	Conforms
9	Resistance to thermal shock	Conforms
13	Chemical resistance	Class GHA
14	Stain resistance	Class 5

Important information - Metallic tiles

The special metallic glaze of these tiles is particularly acid-sensitive. Anti-limescale products should not be used for ordinary maintenance. We recommend to use a natural cleaner such as Fila Cleaner.

Do not use aggressive cleaning products such as bleach or ammonia.

Complaints due to a laying or fixing mistakes will not be accepted.

Sustainability information



Cleaning and maintenance advice

Before grouting *crackle tiles

A pre grout protector Fila PRW200 is advised to protect the tiles; this is a temporary seal that when cleaning the grout will wash off.

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.

Product: Cloth

Impregnating *crackle tiles

It is also recommended to seal the body of the crackle effect tiles with Fila MP90.

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.

Product: Cleaner Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.