

Material: **Porcelain** | Appearance: **Terracotta** | Application: **Walls and floors**



Flims

Flims is inspired by Tuscan architecture and design. The collection is available in a 125×250mm format in four strongly stonewashed nuances. Colour variations includes shades of beige, brown, gray, and pink, among other earthy tones, contributing to creating a more dynamic appearance. They incorporate speckles, spots, and small surface imperfections that add a touch of authenticity and rusticity to the overall look. These features contribute to giving the floors a lived-in and natural appearance. Suitable for both internal and external applications.



Shade variation: V4 extreme



SFCC45928




SFCC45929



SFCC45930



SFCC45931



	Sizes (mm)	> <	Finishes
1	125x250	9mm	R11/C
2	150x300x40	9mm	R11/C



LRV and PTV values can vary batch to batch, please contact for advice.
Switch colours may vary, samples should be requested.



www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:    

Material: **Porcelain** | Appearance: **Terracotta** | Application: **Walls and floors**



Flims



Above
Flims SFCC45928

Right
Flims Mix



Above:
Flims SFCC45930

LRV and PTV values can vary batch to batch, please contact for advice.
Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk

Find us on:    



Flims

Technical data sheet - ISO 10545 average values

2	Sizes	Conforms
3	Water absorption	$\leq 0,5 \%$
4	Modulus of rupture Breaking strength	$R \geq 35 \text{ N/mm}^2$ $S \geq 1300 \text{ n}$
8	Linear thermal expansion	$< 9 \times 10^{-6} \text{ } ^\circ\text{C}^{-1}$
9	Thermal shock resistance	Resistant
11	Crazing resistance	Resistant
12	Frost resistance	Resistant
13	Chemical resistance	CLASS GB MIN.
14	Stain resistance	CLASS 5 MIN.
	Slip resistance	R11/C

LRV and PTV values can vary batch to batch, please contact for advice.
Swatch colours may vary, samples should be requested.

Sustainability information



Cleaning and maintenance advice

Initial washing

The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.
Product: Deterdek Pro

Routine maintenance

The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.
Product: Cleaner Pro

Special maintenance

Special maintenance is carried out in case of very stubborn dirt, when the routine maintenance is not enough to restore the original look of the surface.
Product: PS/87 Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.