Material: **Ceramic** | Appearance: **Earthy tones** | Application: **Walls**

2 Colours | 1 Finish | 5 Tile sizes

Terrosa


Terrosa presents a range of earthy ceramic wall tiles, designed to bring natural warmth and understated elegance to interiors. Featuring a smooth matt finish, these tiles exude a soft, contemporary charm, perfect for creating serene and grounded spaces. They are available in versatile formats, including 75x300mm and prescored sizes, allowing for creative and flexible installation options.

ISO 14001 | EPD VERIFIED ISO 14025

Shade variation: V2 moderate



SCDC47157 | SCDC47158 | SCDC47157T1 | SCDC47158T1



	Sizes (mm)	>||<	Finishes
1	100x100 PRESCORED on 200x200	7.8mm	Matt
2	50x200 PRESCORED on 200x200	7.8mm	Matt
3	25x200 PRESCORED on 200x200	7.8mm	Matt
4	75x300	8.4mm	Matt
5	75x300 T1	8.4mm	Matt T1


Terrosa SCDC47158

Grestec

LRV and PTV values can vary batch to batch, please contact for advice. PTV values refer to Slider 96 (shod) – Wet (unless stated). Swatch colours may vary, samples should be requested.

www.grestec.co.uk | T: 0345 130 2241 | E: sales@grestec.co.uk
Find us on:

Terrosa



Above
Terrosa SCDC47158



Above
Terrosa SCDC47157

LRV and PTV values can vary batch to batch, please contact for advice. PTV values refer to Slider 96 (shod) – Wet (unless stated). Swatch colours may vary, samples should be requested.

Terrosa

Technical data sheet - ISO 10545 average values

2	Sizes	**Conforms**
3	Water absorption	**15%**
4	Flexion resistance	**>23 N/mm²**
8	Linear thermal expansion	**< 7·10-6 /°C**
9	Thermal impact resistance	**Conforms**
10	Expansion due to moisture	**<0.6%**
11	Crazing resistance	**Conforms**
12	Frost resistance	**Conforms**
13	Chemical resistance	**GLA - GHA - GA**
14	Stain resistance	**Class 5**

Sustainability information

Cleaning and maintenance advice

Initial washing
The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.
Product: Cloth

Routine maintenance
The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.
Product: Cleaner Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.

LRV and PTV values can vary batch to batch, please contact for advice. PTV values refer to Slider 96 (shod) – Wet (unless stated). Swatch colours may vary, samples should be requested.