Crest

13 Colours | **1** Finish | **2** Size

Crest is a glazed porcelain tile collection designed to bring architectural depth and dynamic motion to feature walls. Engineered with a pre-mixed balance of concave, flat, and convex surface profiles, Crest catches surrounding light to create a fluid, tactile three-dimensional finish.



RBHF55333
LRV 63



RBHF55334
LRV 50



RBHF55335
LRV 40



RBHF55336
LRV 36



RBHF55337
LRV 28



RBHF55338
LRV 21



RBHF55339
LRV 10




RBHF55340
LRV 41



RBHF55341
LRV 14



RBHF55342
LRV 54



RBHF55343
LRV 16



RBHF55344
LRV 13



RBHF55345


Grestec

0345 130 2241 | sales@grestec.co.uk | www.grestec.co.uk



Crest Mix

Crest



Flat *Concave* *Convex*

Size (mm)		Thickness	Finishes
1	48×200 mix *	9.5	Gloss
2	50×200×48 ANG	9.5	Gloss
3	14×200 QR	9.5	Gloss

* Supplied in a pre-mixed balance of concave (40–50%), flat (25–30%), and convex (25–30%) tiles, allowing light and shadow to create a fluid, three-dimensional surface.



Crest RBHF55345

0345 130 2241 | sales@grestec.co.uk | www.grestec.co.uk

Crest



Above: Crest Mix
Right: Crest RBHF55333, RBHF55339





Above: Crest Mix

Crest

ISO 10545 Results

2	**Sizes**	Conforms
3	**Water absorption**	< 0.15%
4	**Breaking strength** **Modulus of rupture**	Conforms >50 N/mm2
8	**Linear Thermal Expansion**	α ≤ 7.1×10-6 °C-1
9	**Thermal Shock Resistance**	Resistant
12	**Frost Resistance**	Resistant
13	**Chemical Resistance**	LA - HA
14	**Stain Resistance**	Class 5

Cleaning and maintenance advice

Initial washing
The initial washing is fundamental for good treatment results. The initial washing is aimed at removing any laying residues and building grime.
Product: Cloth

Routine maintenance
The aim of the routine maintenance is to remove dirt and scuff marks. Must be carried out regularly.
Product: Cleaner Pro

Please see www.filasolutions.com for methods of use, dilution and coverage.

LRVs and PTVs

LRV and PTV values may vary between batches; please contact us for guidance.

Document + web colours

Swatch colours may differ from final production, samples are recommended.

Sustainability

ISO 14001 | EPD VERIFIED ISO 14025 | 60% RECYCLED MATERIAL

Shade variation

V2